




DCA 2000Y AIR COOLED - NON WATER HEATING DEHUMIDIFIER

DCA 2000YWH WATER HEATING ASSIST DEHUMIDIFIER

PERFORMANCE



Performance	82DB / 50% R.H.	82DB / 60% R.H.	Notes
Moisture Removal, LB/HR	18.5	23.6	1
Net Sensible Cooling, MBH	28.6	25.4	2
Net Reheat, MBH	30.6	36.5	3
Water Heating, MBH (Water Heating Models Only)	60.2	62.5	4

Notes:

1. Reheat mode assuming 1050 BTU/lb
2. Cooling mode with remote condenser at 95F.
3. Defined as sum of latent and compressor input. Use dehumidifier for supplemental heat only.
4. Assuming 85F entering water temperature.
5. For conditions and data not shown contact the factory

CAUTIONS: The reheat capacity rating includes latent recovery and heat of compression. It is recommended that dehumidifier be used for supplemental heat only. The cooling capacity is based on an ambient temperature of 95°F. As outside conditions vary, so will the performance of the dehumidifier. Ratings are subject to change without notice.

DCA 2000Y AIR COOLED - NON WATER HEATING DEHUMIDIFIER

DCA 2000YWH WATER HEATING ASSIST

DESIGN SPECIFICATIONS

Electrical	208/230V	208/230V	460V	575V
Phase/Hz	1/60	3/60	3/60	3/60
Compressor B.T.U.	49,800	49,800	49,800	49,800
Compressor RLA	21.8	16.0	7.7	6.4
Compressor LRA	143	156.4	69	47.8
Blower Motor HP	1.5	1.5	1.5	1.5
Blower Motor FLA	6.2	4.5	2.2	1.9
Unit FLA	29.4	21.9	10.6	8.9
Maximum Fuse Size	50	35	17.5	15
Minimum Circuit Ampacity	34.9	25.9	12.5	10.5
Operating KW	5.04	5.02	4.99	5.11

CFM.....	2000
External Static Pressure.....	1.00" H ₂ O
Refrigerant.....	R-454B (Factory Charged 25 lbs.)
Compressor Type.....	Scroll
DCA 2000Y Filter (Qty: 2).....	18"x25"x1" Fiberglass
DCA 2000YWH Filter (Qty: 2).....	20"x25"x1" Fiberglass
Drain Connection.....	1" Bar Drain
DCA 2000Y Weight.....	540 lbs.
DCA 2000YWH Weight.....	700 lbs.
Liquid Inlet [inches O.D.] (up to 50') ¹	0.5
Hot Gas Outlet [inches O.D.] (up to 50') ¹	0.75
Water Inlet [inches O.D.].....	1.125
Water Outlet [inches O.D.].....	1.125
Water Flow G.P.M. ²	8.5
Pressure Drop (Ft. WC) ²	8.5

¹ Over 50ft contact factory

² Water Flow data based on 60% RH + Return Air 82°F and Pool Water at 85°F

STANDARD FEATURES

- Listed To UL 60335-2-40
- 3 Year Part Warranty
- Single Refrigeration Circuit
- Single Scroll Compressor
- Powder Coated, Galvannealed Steel Cabinet
- Low Ambient Head Pressure Control
- Remote Condenser Ready
- Rifle Tube Refrigeration Coils
- TEFC Blower Motor
- Stainless Steel Condensate Drain Pan
- Standard Microprocessor Control System (WH Models Only)
- ElectroFin Coated Coils

OPTIONAL FEATURES

- Right Side Component Service Access
- Top or Bottom Discharge (Not Field Convertible)
- Extended Surface Filters 2" & 4"
- Outdoor Installation Package
- Outdoor Make Up Air Assembly with Damper & Filter
- External Static Upgrade
- Water Cooled Condenser For Water Heating Or A/C Available
- Motorized Evaporator Bypass Damper
- Remote Ready Delete
- Defrost Timer Package
- Control Options
- Space Heating Options Available
- Other Options Available