




**DCA 4800Y AIR COOLED - NON WATER HEATING DEHUMIDIFIER**

**DCA 4800YWH WATER HEATING ASSIST DEHUMIDIFIER**

**PERFORMANCE**



Performance	82DB / 50% R.H.	82DB / 60% R.H.	Notes
Moisture Removal, LB/HR	45.9	58.6	1
Net Sensible Cooling, MBH	72.3	63.7	2
Net Reheat, MBH	77.3	91.9	3
Water Heating, MBH (Water Heating Models Only)	150.8	155.9	4

Notes:

1. Reheat mode assuming 1050 BTU/lb
2. Cooling mode with remote condenser at 95F.
3. Defined as sum of latent and compressor input. Use dehumidifier for supplemental heat only.
4. Assuming 85F entering water temperature.
5. For conditions and data not shown contact the factory

CAUTIONS: The reheat capacity rating includes latent recovery and heat of compression. It is recommended that dehumidifier be used for supplemental heat only. The cooling capacity is based on an ambient temperature of 95°F. As outside conditions vary, so will the performance of the dehumidifier. Ratings are subject to change without notice.

## DCA 4800Y AIR COOLED - NON WATER HEATING DEHUMIDIFIER

## DCA 4800YWH WATER HEATING ASSIST

### DESIGN SPECIFICATIONS

Electrical	208/230V	460V	575V
Phase/Hz	3/60	3/60	3/60
Compressor B.T.U.	125,000	125,000	125,000
Compressor RLA	33.3	15.4	12.9
Compressor LRA	255	140	107.6
Blower Motor HP	3	3	3
Blower Motor FLA	9.0	4.2	3.3
Unit FLA	44.0	20.4	16.9
Maximum Fuse Size	70	35	30
Minimum Circuit Ampacity	52.3	24.3	20.1
Operating KW	11.94	11.76	11.71

CFM.....	4800
External Static Pressure.....	0.50" H <sub>2</sub> O
Refrigerant.....	R-454B (Factory Charged 65 lbs.)
Compressor Type.....	Scroll
Filter (Quantity: 4).....	20"x25"x1" Fiberglass
Drain Connection.....	1" Bar Drain
DCA 4800Y Weight.....	1320 lbs.
DCA 4800YWH Weight.....	1580 lbs.
Liquid Inlet [inches O.D.] (up to 50') <sup>1</sup> .....	0.75
Hot Gas Outlet [inches O.D.] (up to 50') <sup>1</sup> .....	1.125
Water Inlet [inches O.D.].....	1.375
Water Outlet [inches O.D.].....	1.375
Water Flow G.P.M. <sup>2</sup> .....	23.0
Pressure Drop (Ft. WC) <sup>2</sup> .....	7.8

<sup>1</sup> Over 50ft contact factory

<sup>2</sup> Water Flow data based on 60% RH + Return Air 82°F and Pool Water at 85°F

### STANDARD FEATURES

- Listed To UL 60335-2-40
- 3 Year Part Warranty
- Single Refrigeration Circuit
- Single Scroll Compressor
- Powder Coated, Galvannealed Steel Cabinet
- Low Ambient Head Pressure Control
- Remote Condenser Ready
- Rifle Tube Refrigeration Coils
- TEFC Blower Motor
- Stainless Steel Condensate Drain Pan
- Standard Microprocessor Control System
- Motorized Evaporator Bypass Damper
- ElectroFin Coated Coils

### OPTIONAL FEATURES

- Right Side Component Service Access
- Top or Bottom Discharge (Not Field Convertible)
- Extended Surface Filters 2" & 4"
- Outdoor Installation Package
- Outdoor Make Up Air Assembly with Damper & Filter
- External Static Upgrade
- Water Cooled Condenser For Water Heating Or A/C Available
- Remote Ready Delete
- Defrost Timer Package
- Control Options
- Space Heating Options Available
- Other Options Available